





THE FIRST. THE BEST. AND BETTER THAN EVER.

For more than two decades, Trail King's Advantage Plus! Hydraulic Detachable Gooseneck (HDG) trailer has been North America's best-selling detachable lowboy...and for good reason. Engineered to make unhooking, loading/unloading, and hooking up again a simple one-person operation, the Advantage Plus! HDG has become the "go to" choice for construction professionals. The HDG's dependable load-hauling strength, durability, and versatility can stand up to any challenge...even "tough to scale" loads.

The Trail King Advantage Plus! HDG...destined to be the best detachable lowboy you'll ever own.





Adjustable Arched Gooseneck

The new arched design provides ample truck frame clearance, even at the lowest king pin height setting. The five-position gooseneck door adjustment allows for a full 6" range of king pin height settings. The notched setting control bar for the control handle takes the guesswork out of setting the gooseneck doors in the desired position.



Outrigger Construction

I-beam style outriggers are mounted on the top and bottom flange and span the entire width of the side beam for optimum strength and support. Heavy-duty pullout front outriggers provide extra strength at the pivot point where the weight is concentrated during loading. Close-set outriggers at mid-deck prevent planks from tipping up when the load rolls over them.



V-Shaped Guide

The V-shaped guide directs the gooseneck into position during hook-up, making the coupling process a quick easy one-person operation. The guide rim above the pin hole further prevents the main pin from uncoupling during transit.



Safety Lock

When the gooseneck cylinder doors are closed in the transit position, a safety pin automatically locks the main pin in place so that it cannot jump out of the pin hole and accidentally disconnect the trailer.



Double-Hinged Ramp and Support Ledge

The 31" front loading ramps are doublehinged and reinforced with a support ledge for added strength. Because both hinges rest on the ledge, even heavy track-type equipment can be loaded without risk of "peeling off" the loading ramp.



Knuckle and Boom Troughs, 3rd Lift Axle

Lowered cross members are covered with 1/4" MF80 steel for a knuckle trough in the rear deck area. Lowered cross members through the entire wheel area, including a lowered center section in the rear channel, are covered with 10-ga. steel. A third axle with lift is standard equipment on TK102HDG and TK110HDG models.




Adjustable Ride Height Control

Adjustable ride height control is standard on TK102HDG and TK110HDG models, with the controls conveniently located near the rear tail channel.




Sealed Electrical System


Rubber-mounted LED lights are standard, as well as a sealed "plug and play" electrical system. Rubber grommets protect the wiring wherever it runs through the frame. And should the operator forget to disconnect the lines before detaching the gooseneck from the bed, a replaceable jumper cable between the neck and the deck makes replacing a damaged line easy and convenient.




One-Piece Construction

Trail King I-beams are constructed of one-piece web and flange material and welded on all four corners to seal and protect the seams from rust. The entire trailer is primed and painted with a two-component polyurethane primer and paint before decking and air, hydraulic, and electrical lines are installed, for complete protection from the elements — even in places you can't see.







Products shown may feature optional equipment. Available specifications are subject to change without notice.

TRHUG STANDARD EQUIPMENT	TK/UHDG	TK102HDG	IKTTUHDG
Capacity (in 12')	70,000 lbs.	102,000 lbs	110,000 lbs.
10' 7" gooseneck (16" KP setting with 82" swing clearance)	Χ	Χ	-
13' 0" gooseneck (16" KP setting with 110" swing clearance)	-	-	Χ
2nd king pin setting (40" KP setting with 86" swing clearance)	-	-	Χ
Deck length	24' 0"	25' 9"	25' 9"
1½" oak decking (raised) (NET)	Χ	-	-
1 3/4" apitong decking (raised) (NET)	-	Χ	Χ
25,000 lb. (5/8" wall) axles	2	3	3
3rd axle air lift	-	Χ	Χ
Axle spacing	50"	55"	55"
Anti-lock brake system	Χ	-	-
Frame reinforced for single axle booster or flip axle	-	-	Χ

TKHDG STANDARD EQUIPMENT On All Models:

CTANDADD EQUIDMENT

- 50" loaded 5th wheel height
- Gooseneck arched for increased truck frame clearance
- 5-position gooseneck height adjustment +/- 3"
- Hydraulic self-lifting detachable gooseneck (has ability to lift above or below transport positions)
- Hydraulic gooseneck support arm
- Patented air-activated, self-locking pin on gooseneck (positive lock)
- Gooseneck does not require ground-bearing pads for lifting
- 31" front loading ramps
- 102" overall deck width
- 24" loaded deck height
- 4-beam main frame construction
- 10" I-beam cross members on 24" centers (4" stub crossmembers for 12" centers in outer bays)
- 100,000 / 80,000 PSI yield strength steel construction
- 0.5" x 5" outside top flanges
- Swing-out outriggers with planks
- Pullout HD outrigger at front, double swing-outs at center
- 14 D-rings (bent style) on deck, 2 (straight) on wheel area
- Knuckle trough at rear of deck (72" long, covered w/ 0.25" MF80 steel)

- Full depth boom trough in wheel area (covered w/10-ga. MF80 steel)
- Triangle cut-outs on deck and bolsters
- 16.5" x 7" air brakes w/ outboard drums
- 8.25 x 22.5 10-hole pilot mount steel disc wheels
- 255/70R 22.5 16PR radial tires (H)
- Oil seals, one-piece
- Air ride suspension w/ raising and lowering (raising/lowering optional on TK70HDG)
- Front bolsters
- LED lights (50 state legal)
- Mid-turn signal/clearance lights
- Tail lights, (3) per side (amber in center)
- Rubber-mounted sealed lights and sealed harness system
- Air, electrical, and hydraulics installed after paint
- Liquid-filled air gauge
- Flag holders, front of deck and rear of trailer
- Wide Load sign brackets
- Mud flans
- Media-blasted prior to 2-part polyurethane primer and paint

See your local dealer for full list of available options.

PEOPLE. PRODUCT. PERFORMANCE.

COMPREHENSIVE SUPPORT. UNMATCHED SERVICE.

Whether you own a premium Trail King trailer or you are looking to own one, you can still have access to our comprehensive PEAK PERFORMANCE™ Aftermarket Programs:



Instantly access over 10,000 on-hand parts and a variety of online tools. All Trail King Certified dealers, fleets, and service facilities can place same-day shipping orders for convenient and efficient ordering. Customers looking for more information can contact a local Trail King dealer or submit direct inquires to **trailkingpartssupport@trailking.com**.



Extend the life of your trailer and increase future resale value by restoring it to nearpeak performance through Trail King's factory refurbishment program. Customers can request a free estimate for comprehensive refurbishments or specified repairs by visiting **www.tkpeakperformance.com**. Our expert technicians specialize in Trail King equipment, but we also welcome other trailer brands.



Competitive rates and flexible terms designed to make a Trail King purchase affordable, convenient, and secure. Trail King's innovative payment program operates with an understanding of the changing demands a customer's business faces. Our full suite of financing structures, including Loans, Finance Leases, and TRAC Leases, makes it easier than ever before to own a Trail King trailer.

Trail King is the leading manufacturer of open deck and materials hauling trailers for the asphalt paving, construction, commercial hauling, agriculture, and specialized transport industries. With a network of almost 400 dealer locations across the U.S. and Canada, Trail King is there when you need us. Our dedicated teams of customer service professionals are available 24/7 to serve you.

We know that your bottom line is important to you and it's our commitment to make sure you achieve the lowest cost of ownership with the highest quality trailers offered in the market.

A Trail King trailer won't just get the job done — it will get the job done right.











121918-TKI

300 East Norway Ave. Mitchell, SD 57301 | 800-843-3324 | www.trailking.com