



## STANDARD FEATURES

**A TRAIL KING TILT.  
NOT YOUR AVERAGE ANGLE.**



### Safety Chains

Heavy-duty safety chains with GVWR-rated grab hooks are built tough for years of dependable service.

### Drop-Leg Jack

Bolt-on 25,000 lb 2-speed single-leg jack with drop leg.

### Safety Headboard

The safety headboard provides extra dimension of safety and load-hauling security.

### Deck Lock

Shown with optional air-operated deck lock.

### I-Beam Crossmembers

Crossmembers consist of 80,000 psi yield beams spaced for maximum strength and deck life.

### Heavy-Duty Bent D-Rings

Forged D-rings for your trailer to handle even your toughest hauling requirements.



### Platform Cushioning Cylinders

Dual platform cushioning cylinders make loading and unloading a smooth operation.



### Adjustable Hitch

Accommodate a wide variety of towing vehicles with an adjustable 4-bolt hitch rated for the full GVWR of the trailer.



### Protected Electrical System

Features rubber-mounted, shock-proof, sealed lights and rubber grommets for all wiring through the frame for longer, trouble-free, low-maintenance performance life.



### Adjustable Platform Lock

Keep your deck from accidentally tilting while in the transport mode with the adjustable platform lock mechanism and safety lock pin.



### Break-Away System

Sealed electric break-away system on TKT24 models with electric brakes located in tongue area.



### Deck Counterweights

Smoother tilt operation with built-in counterweights.



### Fold-Down Approach Plate

Fold-down approach plate is designed to meet U.S. Federal under-ride protection requirements. It also achieves the lowest possible load angles and provides extra protection for tail lights.



### Oak Decking

All TKT models come with 1.5" nominal oak decking that is double screwed to crossmembers to prevent cupping. This deck will stand up to years of rugged service. Optional apitong decking available.

TKTLP STANDARD EQUIPMENT	TKT24LP	TKT40LP	TKT50LP	TKT60LP
Payload Capacity	24,000 lb.	40,000 lb.	50,000 lb.	60,000 lb.
5' Tongue Length	X	X	X	X
Pintle Eye Hitch (Adjustable Height)	19.5" to 30.5"	18.5" to 30"	18.5" to 30"	18.5" to 30"
25,000 lb. two-speed single-leg jack	X	X	X	X
Deck Length (Stationary / Tilt)	4' Stat / 24' Tilt	4' Stat / 24' Tilt	6' Stat / 24' Tilt	6' Stat / 24' Tilt
Deck Width	102"	102"	102"	102"
Loaded Deck Height	34"	33"	33"	33.5"
Structural Steel Main Frame	X	X	X	X
1.5" Oak (Raised) Decking	X	X	X	X
(12) D-Rings: (4) on Stationary Deck - (8) on Tilt Deck	X	X	X	X
12 Degree Tilted Deck Slope	X	X	X	X
Hydraulic Cushioning Cylinder	2	2	2	2
Manual Deck Lock	X	X	X	X
Fold-Down Approach & Under Ride Protection	X	X	X	X
Floor Plate on the Approach & Fold-Down	0.25"	0.25"	0.25"	0.25"
Axles	(2) 12,000 lb.	(2) 22,500 lb.	(3) 22,500 lb.	(3) 22,500 lb.
Suspension	Hutch 9700	Hutch 9700	Hutch 9700	Hutch 9700
Brakes	Electric	12.25" x 7.5"	12.25" x 7.5"	12.25" x 7.5"
ABS	N/A	4S2M	4S2M	4S2M
Dual Steel Disc Wheels (8 Hole)	6" x 16"	6.75" x 17.5"	6.75" x 17.5"	6.75" x 17.5"
Tires	235/80R x 16	215/75R x 17.5	215/75R x 17.5	235/70R x 17.5
Safety Chains with Grab Hooks	X	X	X	X
Lockable Toolbox	X	X	X	X
Headboard	X	X	X	X
Registration Holder	X	X	X	X
LED Lights	X	X	X	X
Rubber Mounted Sealed Lights w/ Sealed Harness System	X	X	X	X
Electrical System per DOT Regulations	X	X	X	X
Mud Flaps	X	X	X	X
Red and White Conspicuity Markings	X	X	X	X
Trail King 2-Part Epoxy Primer and Urethane Top Coat Paint	X	X	X	X

*\*See your local dealer for full list of available options.*