

Advantage Series OLB Live Bottom Trailer

Field-tested and proven for over 20 years, the OLB's direct hydrostatic drive, heavy-duty roller chain system, and heat-and-oil-resistant continuous 2-ply rubber belt deliver lean and efficient horizontal discharge of the load in one revolution or less.

Standard Equipment	OLB236NG	OLB336NG	OLB332NG	OLB326NG	OLB426NG	OLB340NG
Capacity	28 cu. yds.	32 cu. yds.	29 cu. yds.	24 cu. yds.	24 cu. yds.	32 cu. yds.
Overall length (A)	40' 7"	40' 7"	36' 7"	30' 7"	30' 7"	44' 7"
Overall height (B)	8' 6" (96" body)	9' 2"	9' 2"	9' 2"	9' 2"	8' 6" (96" body)
Overall width	102"	102"	102"	102"	102"	102"
King pin height (C)	49"	49"	49"	49"	49"	49"
King pin to center of last axle (D)	36'	36'	32'	26'	26'	40'
Number of Axles	2	3	3	3	4	3
Empty weight ±3%	13,350 lbs.	15,390 lbs.	14,900 lbs.	13,850 lbs.	14,980 lbs.	15,900 lbs.

OTHER POPULAR OPTIONS:

- Tarp systems - manual and electric
- Aluminum sheeting/insulation
- Air lift suspensions
- Flow control valve
- Pressurized 12-gal. spray system
- Paint options
- Multiple axle configurations
- Air-Ride suspensions
- Gravel service belt in lieu of heat and oil resistant
- 102" wide body (extra capacity)
- Tire and wheel options

All dimensions are approximate and are subject to change without notice.

See your local dealer for full list of available options.