

<b>STANDARD EQUIPMENT</b>	<b>TK12U</b>	<b>TK14U</b>	<b>TK16U</b>
Payload Capacity	12,000 lb.	14,000 lb.	16,000 lb.
Structural Steel Main Frame	x	x	x
Overall width	102"	102"	102"
Deck Width between Fenders	82"	82"	82"
Overall Deck Length	16'	16"	16'
Loaded Deck Height	23"	23"	23"
Torflex Axles	(2) 7,000 lb.	(2) 7,000 lb.	(2) 7,000 lb.
Electric Brakes on All Axles	x	x	x
12,000 lb. HD Jack with Spring Foot	x	x	x
4-Bolt Pintle Eye Hitch (Adjustable Range)	19" - 23½"	19" - 23½"	19" - 23½"
(6) Tie-Down Brackets	x	x	x
14 Gauge Fenders	x	x	x
5' Self-Supporting Loading Ramps	x	x	x
Single Disc Wheels (8 Hole)	x	x	x
Tires	235/80R x 16	215/75R x 17.5	215/75R x 17.5
1½" Oak Decking (Raised)	x	x	x
Safety Chains with Grab Hooks	x	x	x
Headboard	x	x	x
Breakaway Switch	x	x	x
Electrical System per DOT Regulations	x	x	x
Red and White Conspicuity Markings	x	x	x
Trail King 2-Part Polyurethane Primer & Paint	x	x	x

**See your local dealer for full list of available options.**