

Standard Equipment	APB 1033	APB 1633E
Capacity	1033 cubic feet	1633 cubic feet
Kingpin to Center of Last Axle	38' 4" (21" KP setting)	38' 4" (21" KP setting)
Overall Length	42' 0"	42' 8"
Overall Width	96"	102"
Overall Height	11' 6" (w/ 48" fifth wheel)	13' 1" (w/ 48" fifth wheel)
# of Hopper, 45° Vessel	3	4
# of 20" Manholes w/ Nylon Wear Plate	2	4

Other Standard Equipment		
Standard Fifth Wheel (Bolted & Adjustable)	8" x 21' Aluminum Hose Tube - Curbside	
Aluminum End Frames	Tandem Axle Suspensions: (2) 23k Intraax AANT Ride	
Aluminum Struts	Soft Coated Suspensions	
Non Food Grade w/ Standard Finish	P Spindle Axles	
Toe Rails on Vessel (Extending To Front-Most Manhole)	4S2M Anti-Lock Brake System	
3" Air Inlet on Road Side w/ Male Adaptor	Stemco Platinum Plus Wheel ends 5-yr./500,000-mi.	
Blow Down Line - Road Side Front, Terminating Between Main Frame, Angled Toward Rear	Duralite hub-piloted - Centrifuse Drum	
3 Solimar Fluidizers at Each Hopper w/ Hopper Savers (Controlled By One (1) 3" Butterfly Valve On Front Fender)	8.25 x 22.S Machined Aluminum Wheels	
5" Product Valves	11R22.5 General ST250 14-Ply Radial Tires	
5" Ultraflo #400 (Iron Disc w/ Black Nitrile Seat)	Aluminum Fenders (Front & Rear)	
5" x 4" Aluminum Gravity Drop Tees	Aluminum Air Tank	
4" Sch 40 Aluminum Product Line Piping w/ Grooved Pipe Connectors	Ladder at Rear w/ Hand Rail	
4" Sch 40 Aluminum Discharge Piping w/ Grooved Pipe Connectors, Terminating Below Axles	Gauges on Side of Frame w/ Light	
	LED Lights w/ Sealed Wiring Harness	
	High Mounted 3rd Stop Light	
	Trail King Anti-Sail Mud Flaps	
	Two Speed Landing Gear (crank road side) (Armor Coated Black)	

NOTE: It is recommended that the interior of the vessel be cleaned professionally prior to initial loading to avoid product contamination.

All dimensions are approximate and are subject to change without notice.

See your local dealer for full list of available options.