

STANDARD EQUIPMENT	BDLW22-402	BDLW22-362	BDLW22-403	BDLW26-433
Capacity	22 cu. yds.	22 cu. yds.	22 cu. yds.	26 cu. yds.
Overall length	40'	36'	40'	43'
Overall height	9' 2"	9' 2"	9' 2"	10' 1"
Overall width	102"	102"	102"	102"
KP to center of last axle	36' 6"	32' 6"	36' 6"	39' 6"
Empty weight	9,900 lbs.	9,650 lbs.	11,700 lbs.	12,300 lbs.

STANDARD EQUIPMENT On All Models

16½" air brakes	
8.25 x 22.5 steel disc wheels (hub piloted)	Rubber-mounted sealed beam lights and sealed harness system
Dura-lite hubs/centrifuse drums	Mid-turn signal/clearance lights
Multi-leaf spring suspension	Electrical system per DOT regulations
18" king pin setting	7-pole electrical socket
Oscillating kingpin plate	Red & white conspicuity markings
100,000/175,000 psi high yield steel unitized frame construction	8" composite cylinders
102" wide	Variable flow gate control
Telescopic pin-type park stands	Bolt-on push block/bumper

OPTIONAL FEATURES

20' and 43' overall lengths	Pup trailers available
6-pole electrical socket	Single and tandem dollies
3 rd tail light package	Tire and wheel options
Air-ride suspension	Side bards/tarp systems
Sloped cover front and rear	

See your local dealer for full list of available options.