



STANDARD FEATURES

BUILT TO OVERCOME

EVERY DAY CHALLENGES.



Safety Chains

Heavy-duty safety chains with GVWR-rated grab hooks are built tough for years of dependable service.

Drop-Leg Jack

Bolt-on 25,000 lb 2-speed single-leg jack with drop leg.

Heavy-Duty Bent D-Rings

Forged D-rings for your trailer to handle even your toughest hauling requirements.



Adjustable Hitch

Accommodate a wide variety of towing vehicles with an adjustable 4-bolt hitch rated for the full GVWR of the trailer.



Toolbox

The conveniently located toolbox is roomy enough to store chains and tools and, because it is lockable, it is secure enough for you to do so with confidence.



Bolt-on Spare Tire Carrier

Optional feature that allows you to safely mount and easily remove a spare tire.



Safety Headboard

The safety headboard provides extra dimension of safety and load-hauling security.



Oak Decking

All TKLP models come with 1.5" nominal oak decking that is double screwed to cross members to prevent cupping. This deck will stand up to years of rugged service. Optional apitong decking available.



Break-Away System

Sealed electric break-away system on TK20/24 models with electric brakes located in tongue area.

Axles, Wheels, and Tires

Truck-type axles and wheels, oil seal hubs, and radial tires are standard equipment. So you not only get the right equipment for the job, you also get less down time, easier maintenance, and long service life.



I-Beam Crossmembers

Crossmembers consist of 80,000 psi yield beams spaced for maximum strength and deck life.



Extended Beavertail

A full 5 or 6 foot beavertail comes standard, allowing for a lower load angle and increased loading ease and safety.

Note: Ramps shown with optional bolt-on knife edge.



Spring-Assist Ramps

Standard self-supporting 5 foot raps with spring-assist are lightweight, strong and easy to handle. Choose between standard ladder-type or optional wood-filled or air-assist ramps.



Protected Electrical System

Features rubber-mounted, shock-proof, sealed lights and rubber grommets for all wiring through the frame for longer, trouble-free, low-maintenance performance life.

TKLP STANDARD EQUIPMENT	TK20LP	TK24LP	TK40LP	TK50LP	TK60LP
Payload Capacity	20,000 lb.	24,000 lb.	40,000 lb.	50,000 lb.	60,000 lb.
5' Tongue Length	X	X	X	X	X
Pintle Eye Hitch (Adjustable Height)	18.75" - 30"	18.75" - 30"	16.5" - 32"	16.5" - 32"	16.5" - 32"
25,000 lb. 2-Speed Single-Leg Jack	X	X	X	X	X
Loaded Deck Height	33"	34"	33"	33"	33.5"
Deck Width	102"	102"	102"	102"	102"
Deck Length (Flat + Beavertail)	24' (19' + 5')	24' (19' + 5')	26' (21' + 5')	30' (25' + 5')	30' (25' + 5')
Structural Steel Main Frame	X	X	X	X	X
1.5" Oak Decking (Raised)	X	X	X	X	X
Self-Cleaning Beavertail (includes mud flaps)	X	X	X	X	X
5' Ladder Style Ramps with Spring Assist	X	X	X	X	X
Maximum Adjustable Ramps	X	X	X	X	X
Suspension	Dexter Slipper Spring	Dexter Slipper Spring	Hutch 9700	Hutch 9700	Hutch 9700
Axles	(2) 10,000 lb.	(2) 12,000 lb.	(2) 22,500 lb.	(3) 22,500 lb.	(3) 22,500 lb.
Brakes	Electric	Electric	12.25" x 7.5"	12.25" x 7.5"	12.25" x 7.5"
ABS	N/A	N/A	4S2M	4S2M	4S2M
Dual Steel Disc Wheels (8 Hole)	6" x 16"	6" x 16"	6.75" x 17.5"	6.75" x 17.5"	6.75" x 17.5"
Tires	235/80R x 16	215/75R x 16	235/80R x 17.5	235/80R x 17.5	235/70R x 17.5
(10) D-Rings	X	X	X	X	X
Safety Chains with Grab Hooks	X	X	X	X	X
Lockable Toolbox	X	X	X	X	X
Headboard	X	X	X	X	X
Registration Holder	X	X	X	X	X
LED Lights	X	X	X	X	X
Electrical System per DOT Regulations	X	X	X	X	X
Red and White Conspicuity Markings	X	X	X	X	X
Trail King 2-Part Epoxy Primer and Urethane Top Coat Paint	X	X	X	X	X

*** See your local dealer for full list of available options.**

Products shown may feature optional equipment. Available specifications are subject to change without notice.