

<b>STANDARD EQUIPMENT</b>	<b>BD22-402</b>	<b>BD22-362</b>	<b>BD22-403</b>	<b>BD22-433</b>
Capacity	22 cu. yds.	22 cu. yds.	22 cu. yds.	22 cu. yds.
Overall length	39' 10"	39' 10"	39' 10"	42' 10"
Overall height	9' 2"	9' 2"	9' 2"	9' 2"
Overall width	102"	102"	102"	102"
KP to center of last axle	36'	32'	36'	39'
Empty weight	12,600 lbs.	12,200 lbs.	14,600 lbs.	14,900 lbs.

#### **STANDARD EQUIPMENT On All Models**

22 cu. yd. hopper	Bolt-on push block/bumper
16½" air brakes	Rubber-mounted sealed beam lights and sealed harness system
8.25 x 22.5 steel disc wheels (hub piloted)	Mid-turn signal/clearance lights
11R22.5 steel disc wheels (F)	3 <sup>rd</sup> tail light package
Oil seals	Electrical system per DOT regulations
Multi-leaf spring suspension	7-pole electrical socket
18" king pin setting	Red & white conspicuity markings
Oscillating kingpin plate	8" air cylinders
100,000/80,000 psi high yield steel unitized frame construction	Open/close gate control from cab – versa valve with handle
102" wide	
Telescopic pin-type park stands	

#### **OPTIONAL FEATURES**

20' and 48' overall lengths	Single point suspension
Variable flow gate control	Pup trailers available
6-pole electrical socket	Single and tandem dollies
Air-ride suspension	Hub and drum options
Sloped cover front and rear	Tire and wheel options

**See your local dealer for full list of available options.**